

Material Safety Data Sheet

Effective: May 2010



SECTION 1 – PRODUCT AND COMPANY INFORMATION

Product Identifier: Ecoustimac Ecocell

Product Name: ECOCELL Acoustic Panels

SECTION 2 – COMPOSITION AND INGREDIENT INFORMATION

COMPONENT/CAS #	% BY WEIGHT	EXPOSURE LIMITS	CANCER DESIGNATION
Newsprint (Cellulose Fiber) #65996-61-4	Not less than 40%	OSHA PEL-TWA=15mg/m ³ TOTAL DUST (PNOR) PNOR – Particulates Not Otherwise Regulated or Nuisance Dust OSHA PEL-TWA=5mg/m ³ total dust (PNOR) Cal OSHA PEL=10mg/m ³ total dust (PNOR) ACGIH TLV-TWA=10mg/m ³ inhalable (PNOS) PNOS – Particulates Not Otherwise Specified ACGIH TLV-TWA=3mg/m ³ respirable (PNOS)	None
PET (Polyethylene terephthalate) #25038-59-9	Not less than 15% Not more than 30%	PEL (OSHA): None Established TLV (ACGIH): None Established AEL* (DuPont): 10 mg/m ³ , 8 Hr. TWA, total dust 5 mg/m ³ , 8 Hr. TWA, respirable dust	None
Boric Acid H₃BO₃ #10043-35-3	Not more than 15%	OSHA PEL-TWA=15mg/m ³ total dust (PNOR) OSHA PEL-TWA=5mg/m ³ respirable fraction (PNOR) Cal OSHA PEL=5mg/m ³ ACGIH TLV-TWA=2mg/m ³ ACGIH TLV-STEL=6mg/m ³ (inhalable fraction - Borate Compounds, inorganic)	None
Jute	Not more than 15%	Not established	None
Cotton	Not more than 15%	OSHA PEL- 15mg/m ³ Respirable 5mg/m ³ PNOR	None

HMIS Rating		National Fire Protection Association (NFPA)	
Health	1	Red (Flammability)	1
Flammability	1	Yellow (Reactivity)	0
Reactivity	0	Blue (Acute Health)	1*
Personal Protection	E	* Chronic Effects	

SECTION 3 – HAZARD IDENTIFICATION

Emergency Overview

Avoid extreme heat and open flame. May emit carbon monoxide gas and boric acid and other hazardous particulates during thermal decomposition. This product is a finely divided, light gray material with no perceptible odor. It presents no unusual hazard if involved in a fire.

Physical Characteristics

Material Safety Data Sheet

Effective: May 2010



Boiling Point	Not Applicable
Vapor Pressure (mm Hg)	Not Applicable
Vapor Density	Not Applicable
Solubility in Water	Insoluble: Dispersible
Specific Gravity (H₂O=1)	Not Applicable
Reactivity in Water	None
Melting Point	Not Applicable

Potential Health Effects

Inhalation	Slightly irritating to upper respiratory system. Persons with respiratory problems should avoid breathing dust.
Eyes	Slight irritant. In case of eye contact, flush with water.
Ingestion	Small amounts are not likely to cause harm. Ingestion of large amounts may cause rash, diarrhea, and nausea.
Skin	Does not normally irritate skin. In case of broken skin, wear gloves and wash dust from skin with soap and plenty of water. Large amounts absorbed into bloodstream may cause rash, skin peeling, diarrhea, nausea, and dizziness.
Acute	Not anticipated as discussed above.
Chronic	None
Cancer	Neither the end product nor any of its components.

SECTION 4 – FIRST AID

Eyes	For dust exposure, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
Skin	If skin is exposed, wash with soap and large amounts of water. If irritation persists, seek medical attention.
Inhalation	If irritation or difficulty in breathing occurs, remove to fresh air. Seek medical attention if conditions persist.
Ingestion	Symptoms may include diarrhea, nausea and vomiting. Seek medical attention if material was ingested and symptoms persist.
Note to Physicians	Exposure to dust may aggravate symptoms of persons with pre-existing respiratory tract conditions and may cause skin and gastrointestinal symptoms.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point	Not Applicable
Combustible	Material may decompose on contact with extreme temperatures and open flames.
Flammable Limits	LEL: Not applicable UEL: Not applicable
Auto ignition Temperature	Not determined
Explosion Hazard	None expected for product based on particle size. Note: Airborne concentrations for combustible dust, when combined with an ignition source, can create an explosion hazard if the dust concentrations exceed 15 mg/m ³ .
Extinguishing Media	Water, dry chemical and other agents rated for a wood fire (Type A fire). Use Type A rated extinguisher.
Fire Fighting Instructions	Evacuate the area and notify the fire department. If possible, isolate the fire by moving other combustible materials. If the fire is small. Use a hoe-line or extinguisher rated for a Type A fire. If possible, dike and collect water used to fight fires. Fire fighters should wear normal protective equipment (full Bunker gear) and positive-pressure, self-contained breathing apparatus.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Contains water-soluble inorganic mineral salts that may damage trees or vegetation exposed to large quantities. Land: shovel, sweep or vacuum product, place in disposal container. Avoid bodies of water. Water; large quantities may cause localized contamination of surrounding waters depending on the quantity spilled. At high concentrations, may damage localized vegetation, fish and other aquatic life. This product is a non-hazardous waste when spilled or disposed of as defined in the Resource Conservation and Recovery Act (RCRA) regulations (40CFR 261). Refer to regulatory information in Section 15 for additional information regarding EPA and California regulations.

SECTION 7 – HANDLING AND STORAGE

General	No special handling is required. Storage of product in a dry, indoor location is recommended. To maintain product integrity, handle on a first-in-first-out basis. Use good housekeeping and controls so that dust levels are below the exposure limits listed in Section 2.
Storage Temperature	Ambient
Storage Pressure	Atmospheric
Special Sensitivity	None

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Material Safety Data Sheet

Effective: May 2010



General Exposure Controls	No specific controls are needed.
Respiratory Protection	If controls do not maintain nuisance levels below regulatory limits, use a NIOSH approved mask.
Eye Protection	Wear ANSI approved eye protection in excessively dusty environments.
Hand Protection	If skin is broken or sensitive, use gloves.
Other Protective Clothing	None
Ventilation	Normal and adequate ventilation.
Work/Hygienic Practices	Standard hygienic practices.
Occupational Exposure Limits	<i>This product is listed/regulate by OASH, Cal/OSHA as "Particulates Not Otherwise Regulated" or "Nuisance Dust." This product is listed by ACGIH as "Particulates Not Otherwise Specified."</i>

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Gray, odorless fiber	Boiling/Melting Point	Not applicable
Specific Gravity	0.7 compressed	Flash Point	Not applicable
Vapor Pressure	Negligible @ 20° C	Ph	7.2 (2% solution @ 25° C)
Solubility in Water	Product is not soluble	Viscosity	Not applicable

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Hazardous Decomposition Products: None

Hazardous Polymerization: Will not occur

SECTION 11 – TOXICOLOGICAL INFORMATION

BORIC ACID

Eye	Draize test in rabbits produced mild eye irritation effects. No adverse eye effects anticipated.
Skin	Low acute dermal toxicity, LD50 in rabbits is greater than 2000 mg/kg of body weight. Boric acid is poorly absorbed through skin.
Ingestion	TDLo, oral, human, 1' 500 mg/kg, diarrhea, nausea, vomiting, LD50, oral, rat, 2840 mg/kg.
Inhalation	Low acute inhalation toxicity; LC50 in rates is greater than 2.0 mg/L (or g/m ³).
Reproduction	Animal feeding studies in rat, mouse, and dog, at high do, have demonstrated effects of fertility.
Mutagenicity	No mutagenic activity was observed for boric acid in a battery of short-term mutagenicity assays.

SECTION 12- ECOLOGICAL INFORMATION

BORIC ACID

Ecotoxicity	Daphnia magna, 48-hr LC50=133 mg B/L. Trout, 32-day LC50=100 B/L
Chemical Fate Information	Boron is naturally occurring and ubiquitous in the environment. Boric acid decomposes in the environment to natural borate. Boric acid is soluble in water and is leachable through normal soil.

Boric Acid is classified as hazardous under the OSHA Hazard Communication Standard based on animal chronic toxicity studies. Refer to Sections 3 and 11 for details on hazards.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose as a non-hazardous waste.

SECTION 14 – TRANSPORT INFORMATION

May be shipped normally as a non-hazardous material.

SECTION 15 – REGULATORY INFORMATION

Superfund: CERCLA/SARA. This product is not listed under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) or its 1986 amendments, the Superfund Amendments and Reauthorization Act (SARA), including substances listed under Section 313 of SARA, Toxic Chemicals, 42 USC 11023, 40 CFR 372.65; Section 302 of SARA Extremely Hazardous Substances, 42 USC 11002, 40 CFR 355; or the CERCLA Hazardous Substances list, 42 USC 9604, 40 CFR 302.

RCRA: This product is not listed as a hazardous waste under any sections of the Resource Conservation and Recovery Act or regulations (40 CFR 261 et seq.).

Safe Drinking Water Act: This product is not regulated under SDWA, 42 USC 300g-1, 40 CFR 141 et seq. Consult state and local regulations for possible water quality advisories regarding boron. California Proposition 65: This product is not listed on any Proposition 65 lists of carcinogens or reproductive toxicants.

OSHA Carcinogen: Not listed.

Clean Water Act (Federal Water Pollution Control Act): 33 USC 1251 et seq.: This product is not itself a discharge covered by any water quality criteria of Section 304 of CWA, 33 USC 1314. This product is not on the Section 307 List of Priority Pollutants, 33 USC 1317, and 40 CFR 116. This product is not on the Section 311 List of Hazardous Substances, 33 USC 1321, and 40 CFR 116.

TSCA No.: This product does not appear on the EPA TSCA inventory list. Boric acid appears on the EPA TSCA inventory list under CAS Number 10043-35-3.

OSHA/Cal/OSHA: This MSDS document meets the requirements of both OSHA and Cal/OSHA hazard communication standards. Refer to Section 8 for regulatory limits.

IARC: The International Agency for Research on Cancer (of the World Health Organization) does not list or categorize this product as a carcinogen.

NTP Annual Report on Carcinogens: Not listed.

SECTION 16 – OTHER INFORMATION

Information presented herein has been compiled from sources considered dependable and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. The user is responsible to determine the suitability of any material for a specific purpose and adopt necessary safety precautions. We make no warranty as to results to be obtained in using any material and, since conditions or use are not under our control, we must necessarily disclaim all liability with respect to use of any material supplied by us.

ABBREVIATIONS:

CAS	Chemical Abstract Services	OSHA	Occupational Safety and Health Administration
Mg/m³	Milligrams per cubic meter	PNOR	Particulates Not Otherwise Regulated
LCLo	Lethal concentration low	PNOS	Particulates Not Otherwise Specified
LDLo	Lethal dose low	PEL	OSHA Permissible Exposure Limit
LC50	Lethal concentration 50%	Ppm	Parts per million
LD50	Lethal dose 50%	RfD	Reference dose
LOAEL	Lowest Observed Adverse Effect Level	TDL_o	Toxic dose low
Mg.l/H	Milligrams per liter per hour	TDL_o	Toxic dose low
Mg/kg	Milligrams per kilogram	TLV	ACGIH threshold Limit Value
Mg/m³	Milligrams per cubic meter	TWA	8-hour Time Weighted Average Exposure

BIBLIOGRAPHY:

1. The guide to Occupational Exposure Values, American Conference of Government Industrial Hygienists, 1997.
2. Registry of Toxic Effects of Chemical Substances, National Institute of Occupational Safety and Health, Q-1, 1998.
3. Dangerous Properties of Industrial Materials, Sax's, 1997 CD-Folio.
4. Hazardous Substances Data Bank, Canadian Centre for Occupational Health and Safety, Q-1. 1998.
5. Integrated Risk Information System, EPA, on-line.
6. Toxicological Profiles, Agency for Toxic Substances and Disease Registry, U.S. Public Health Service, 1997.
7. TLV's and other Occupational Exposure Values, American Conference of Governmental Industrial Hygienists, 1996.
8. 29 CFR 1910.1000 TABLE Z-1 and Z-3.
9. California OSHA Title 8, Section 5155, Table AC-1.